

IP 705

IP Telephone



The IP 705 is a standard IP Phone designed exclusively for AltiGen IP Phone Systems. The IP 705 provides a subset of the flagship IP 710 VoIP telephone's features while offering the same level of voice quality at a reduced price.

Users have convenient single button access to voicemail, call conferencing, call transferring, redial and call log lists.

With the 2 line liquid crystal display the IP 705 is capable of displaying time, Caller ID name or number, and do-not-disturb and call forwarding status.

Customizing the IP 705. You can personalize the IP 705 with 5 backlit user-defined keys. These programmable keys can be setup for any combination of configurable features like, but not limited to, speed-dialing, extension busy/ringing appearances, call appearances and line appearances.

The IP 705 also supports 3rd party hands free headsets using AltiGen's amplified industry standard RJ9 headset port.

AltiGen also provides you with 7 combined traditional and melodic ring tones which can also be assigned to call, line, and extension appearances on the programmable keys.

Productivity Features:

- ▶ One button access for voice recording to your personal voicemail box or to a centralized server
- ▶ One button access to voicemail
- ▶ 5 user programmable keys for extension, call and line appearances, access to feature codes, and speed dialing
- ▶ Auto answer feature allows calls to be answered automatically to a defined voice device within a specific ring time. Great for call center service agents with headsets or office operators
- ▶ Optional Power over Ethernet (PoE) support



"The available feature set on the IP 705 VoIP telephone brings tremendous value to the table."

John Babin
Capture Technologies, Oakland CA

1-888-ALTIGEN | www.altigen.com

Opportunity is Calling

IP 705 Phone Features:

Part No. ALTI-IP705



ALTIGEN
COMMUNICATIONS



One-touch feature buttons:

- ▶ Redial
- ▶ Hang-up/Release
- ▶ Hold
- ▶ Speaker
- ▶ Mute
- ▶ Flash
- ▶ Transfer
- ▶ Conference
- ▶ Speaker
- ▶ Voicemail
- ▶ Volume control
- ▶ 5 backlit user programmable keys

LCD Module & Keypad:

- ▶ 2 x16 LCD
- ▶ 2 different programmable key template colors

LCD Display Capabilities:

- ▶ Caller ID Name & Number
- ▶ DNIS Name & Number
- ▶ Time display and call timer
- ▶ Message waiting indicator
- ▶ Do-not-disturb and call forwarding status display
- ▶ Activity/presence status display
- ▶ Workgroup statistics
- ▶ Call log
- ▶ And more...

Network Interface:

- ▶ Built-in 10/100 Ethernet switch
- ▶ RJ-45 port x 2 (LAN/PC)

Voice Devices:

- ▶ Handset port
- ▶ RJ-9 industry standard headset ports
- ▶ Hands free speaker phone

General Specifications:

- ▶ Physical Dimensions (HxWxD) 209x200x49 mm
- ▶ Main Body Weight: 823 g (1 lb 13 oz)
- ▶ Handset Weight: 176g (6.2 oz)
- ▶ Operation Temperature: 0 ~ 40o C (32 ~ 104o F)
- ▶ Storage Temperature: -10 ~ 60o C (14 ~ 140o F)
- ▶ Operation Humidity: 5%~90% Non-condensing
- ▶ Wall Mountable



1-888-ALTIGEN | www.altigen.com

Altigen Communications, Inc.

4555 Cushing Parkway
Fremont, CA 94538
Tel: (510) 252-9712
Fax: (510) 252-9738
sales@altigen.com

Opportunity is Calling